



## UC100-1V1S10 All-in-one Box

**UC100** is a multi-functional gateway, which integrates voice service(PSTN and VoIP) and data service(LTE 4G/WCDMA 3G). It provides three voice interfaces (including GSM/LTE, FXS and FXO), offering seamless connectivity to VoIP Network, PLMN and PSTN. Based on SIP, it not only can interact with VoIP network, but also supports types of GSM/WCDMA/LTE frequency ranges, thus meeting the worldwide requirements about the mobile network. UC100 supports WiFi and has high-speed data-handling capacity, allowing users to enjoy high-speed internet surfing through WiFi or the LAN port.

With VPN transparent transfer function, UC100 is ideally suitable for personal use. Meanwhile, it is perfect for small and micro enterprises, providing high-speed internet access, good voice service and messaging service.

### Product Pictures



**UC100**  
Front View



**UC100**  
Rear View

### Key Features

- FXS/FXO/LTE interface on a single device
- Send/receive calls from PSTN/PLMN via FXO
- Flexible dial plan, via time, numbers, source IP etc.
- IVR customization
- High speed NAT forwarding, support WIFI hotspot
- Built-in SIP server, support up to 32 SIP Extensions
- User-friendly web interface, multiple management ways

# UC100-1V1S1O All-in-one Box

## Physical Interfaces

- FXS Port: 1
- FXO Port: 1
- SIM Slot: 1
- **Ethernet Interfaces**  
1WAN&3LAN 10/100 Base-T RJ45
- **WIFI**  
2.4GHz 802.11b/g/n,2T2R

## Voice Capabilities

- VoIP Protocols: SIP over UDP/TCP/TLS,SDP,RTP
- Codecs: G.711a/μ law,G.723.1, G.729A/B, iLBC,G.726
- Silence Suppression
- Comfort Noise Generator(CNG)
- Voice Activity Detection(VAD)
- Echo Cancellation: G.168 with up to 128ms
- Dynamic Jitter Buffer
- Adjustable Gain Control
- Automatic Gain Control (AGC)
- Call Progress Tones: Dial Tone, Ring Back Tone, Busy Tone
- FAX: T.38 and Pass-through
- NAT: STUN/UPnP/Static NAT
- DTMF: RFC2833/SIP Info/In-band

## FXS

- Connector: RJ11
- Caller ID: Bellcore Type 1&2, ETSI,BT,NTT and DTMF
- Answer and Disconnect Signaling: Answer, Disconnect, Busy Tone
- Polarity Reversal
- Hook Flash

## FXO

- Connector: RJ11
- Caller ID: FSK, DTMF
- Polarity Reversal
- Answer Delay
- Busy Tone Detection
- No Current Detection

## Mobile

- GSM/GPRS/EDGE: 900/1800MHz
- WCDMA(3G):  
UMTS/HSDPA/HSPA+ B1/B8  
TD-SCDMA B34/B39
- LTE(4G):  
TDD-LTE B38/B39/B40/B41  
FDD-LTE B1/B3/B7/B8
- SIM/USIM: 1 USIM per Channel
- SIM Card: 1.8V, 3.0V
- Antenna: 3.0dB, SMA Interface
- SMS/USSD

# UC100-1V1S1O All-in-one Box

## Supplementary Services

- Call Forward (Unconditional/No Answer/Busy)
- Call Waiting
- Call Hold
- Call Transfer
- Hotline
- Do-not-disturb
- 3 Way Conference

## Software Features

- SIP Trunk
- Build-in SIP Server with up to 32 SIP Extensions
- Ring Group
- Routing Groups
- Caller/Called Number Manipulation
- Routing Base on Time Period
- Routing Base on Caller/Called Prefixes
- Routing Base on Source Trunks
- Dial Rules
- Failover Routing
- FXO Impedance Auto Match
- IVR Customization
- Auto Attendant Function
- CDRs

## Maintenance

- Web GUI Configuration
- Telnet Management
- Configuration Restore/Backup
- Multiple Languages Supported
- HTTP/HTTPS/FTP Firmware Upgrade
- Auto Provision
- CDR Report and Export
- Syslog
- Ping and Tracert
- Traffic Statistics: TCP,UDP,RTP
- Network Capture
- NTP

## Network

- Access Rules
- DHCP Client/ DHCP Server
- Port Forward, DMZ, Static Routes
- UPnP Client/DDNS
- PPTP/L2TP/OpenVPN Client

## Environmental

- Power Supply: 12VDC, 1A
- Power Consumption: 10W
- Operating Temperature: 0 °C ~ 45 °C  
Storage Temperature: -20 °C ~80 °C
- Humidity: 10%-90% Non-Condensing
- Dimensions (W/D/H): 126×75×25mm
- Unit Weight: 0.7kg

# UC100-1V1S1O All-in-one Box

## Product Information

**UC100-1V1S1O** has several variants model to meet the requirements of our customers.

Model	Description
UC100-1V1S1O	1 LTE, 1 FXS, 1 FXO, WIFI, 1 WAN 3 LAN, Built in SIP Server
UC100-1V1S	1 LTE, 1 FXS, WIFI, 1 WAN 3 LAN, Built-in SIP Server
UC100-1S1O	1 FXS,1 FXO, WIFI, 1 WAN 3 LAN, Built-in SIP Server
UC100-1S	1 FXS, WIFI, 1 WAN 3 LAN, Built-in SIP Server

## About Us

Dinstar has the most complete VOIP gateway products line in China, which covered GSM/CDMA/LTE Wireless Gateway, E1/T1 Trunk Gateway, FXS/FXO Analog Gateway, SIMBANK and SIMCLOUD system etc. Through our increasing innovation ability, excellent user experience, high performance-price ratio and tailored OEM/ODM service, Dinstar products and services have been widely deployed and recognized by telecom operators, system integrators, and enterprises around the world. With company culture of Honesty, Concentration, Innovation and Open-mind, our staffs gather and unify tightly as a team, aim to establish win-win relationships with our customers.

## Contact Us

### Shenzhen Dinstar Co., Ltd.

9<sup>th</sup> Floor, Guoxing Building, Changxing Road, Nanshan District, Shenzhen,  
Guangdong, P.R.China, 518052

Tel.: +86 755 6191 9966 FAX: +86 755 2645 6659

Email: sales@dinstar.com [support@dinstar.com](mailto:support@dinstar.com)

Website: www.dinstar.com